



MAINTENANCE AND CLEANING INSTRUCTIONS

1. REMOVE FILTER/ PRE-FILTER AND PLACE IN PLASTIC TUB OR BUCKET.
2. FOR A " *QUICK CLEAN* " SOAK FILTER IN A QUALITY DEGREASER SUCH AS MAXIMA CLEAN-UP, SIMPLE GREEN OR A MILD DETERGENT.

NOTE: SOAKING FILTER AND PRE-FILTER IN A TUB OF VERY HOT WATER AND A SCOOP OF LAUNDRY DETERGENT ALSO WORK VERY WELL.
3. SOAK/WASH WITH HOT SOAPY WATER, RINSE AND LET FILTER AIR DRY COMPLETELY.
4. APPLY A COAT (DO NOT SATURATE) OF AERESOL/ SPRAY FABRIC AIR FILTER OIL. RECOMMENDED - MAXIMA, PJ1, BELL RAY OR K&N.
5. RE INSTALL CLEAN AIR FILTER TO HIGH FLOW ADAPTER AND TIGHTEN SECURING CLAMP.

IMPORTANT
CLEAN YOUR VELOCITY FILTER AFTER EVERY FEW HOURS OF RIDING FOR PROPER PROTECTION OF YOUR ENGINE.

TIP: A CLEAN AIR FILTER AND REGULAR OIL CHANGES ARE THE MOST IMPORTANT THINGS YOU CAN DO TO KEEP YOUR HIGH PERFORMANCE ENGINE RUNNING AT OPTIMUM PERFORMANCE

